

SC601 Product Series Hardware Specification

Model	SC601
Max. FPS	60/50fps @ 1920 x1080p
Recording Mode	Hardware Compression, Real-Time Mode
Product Photo	
Input Interfaces	<p>Video</p> <ul style="list-style-type: none"> ● 1 x BNC for 3G / HD / SD-SDI ● 3 x BNC for YPbPr /CVBS/S-Video ● 1 x DVI-I for DVI-D /HDMI and DVI-A/ VGA ● 1 x HDMI <p>Audio</p> <ul style="list-style-type: none"> ● 1 x Stereo audio through ➢ 1 x RCA for Analog L/R audio ➢ SDI/HDMI/DVI-D embedded audio ➢ 1 x 3.5 mm phone jack
Video Feature	<p>H.264/AVC , Main / High Profile Configurable bit rate up to 10Mbps Supported Resolutions</p> <ul style="list-style-type: none"> ● Input: <ul style="list-style-type: none"> ➢ 1920x1080(P60/P50/P30/P25/i60/i50), 1440x1050(P60),1440x900(P60), 1360x768(P60), 1280x1024(P60), 1280x960(P60), 1280x800(P60), 1280x720(P60), 720x576(P50),720x480(P60), 720x576(i50),720x480(i60) ● Output: <ul style="list-style-type: none"> ➢ 1920x1080(P30/P25/i60/i50), 1440x1050(P30),1440x1080(P30),1440x900(P30), 1360x768(P30), 1280x1024(P30), 1280x960(P630), 1280x800(P30), 1280x720(P30), 960x540(P30),720x576(P50),720x480(P30),320x240(P30), 720x576(i50),720x480(i60) ● *Output Include Down Scaling.
Audio Feature	<ul style="list-style-type: none"> ● AAC-LC ● Configurable bit rate range from 32Kbps to 384Kbps ● Sample rate : 48KHz, 16bit
Network Feature	<ul style="list-style-type: none"> ● 1 x RJ45 for 10/100Mbps Ethernet ● DHCP client
Support Streaming protocol	<ul style="list-style-type: none"> ● TS over TCP/UDP (unicast & multicast) ● RTSP over HTTP/TCP/UDP (RTSP Elementary Stream) ● RTMP(Local & Publish) ● HLS

Misc. Features	<ul style="list-style-type: none">● RS-485● 1 x USB 2.0 Host for USB storage● Web UI for system configuration● Firmware upgradable● LED indicator● Status with Power Recycle
Record Format	MP4 / TS
System Requirement	
Power Supply	DC 12V (With DV Adapter)